

## Cleaning - Protecting - Maintaining Porcelain Tiles -indoors/outdoors-

Instructions for vitrified porcelain tiles with matt or polished finishes

Porcelain tiles are made of very fine ceramic materials that are fired at high temperatures. This process leads to very dense, very robust tiles. The right treatment will bring the tiles to their full potential and ensures the ideal properties for many years.

### Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

**1**

#### Initial cleaning of newly installed surfaces *used surfaces: Page 2*


Lithofin FZ Cement Residue Remover leaves a clean and clear surface.



Coverage:  
1Ltr./50m²



Dilute product 1:4  
with water.



Wipe surface with  
solution and scrub.



Rinse well with plenty  
of clear water and  
towel dry.

**Necessary equipment:** bucket, mop and scrubber, squeegee or wet-and-dry vacuum

**2**

#### Protecting against stains preferred treatment for new and polished surfaces

*initial cleaning of used surfaces: Page 2*

Lithofin FZ Stain-Stop >W< (or Lithofin FZ Stain-Stop) renders the surface water and oil repellent



Coverage:  
1Ltr./40m²



Please note.




Pour product in a  
basin or bucket.




Evenly apply with a  
micro-fibre mop and  
allow to remain on the  
surface for 15 min.



Completely remove  
all residues, streaks  
and puddles. Do not  
allow to dry – towel  
finish.



Allow to dry.  
Do not walk on  
surface for approx. 2  
hours.



Protect from water for  
24 hours.

**Necessary equipment:** bucket, applicator or roller, brush, cloth

**3**

#### Regular maintenance *additional maintenance tips: Page 2*


Lithofin FZ Vitra-Clean maintains porcelain tile surfaces.



Add one squirt (20ml)  
to one bucket of  
water.



Wipe surface with  
solution. Remove  
moisture with a well  
wrung-out mop.



Allow to dry. Do not  
walk on surface  
during drying time.

**Necessary equipment:** bucket, mop

**Please follow the detailed instructions on the product labels. *for additional information, please refer to Page 2***

## Newly installed surfaces

Nearly invisible residues of grouting materials and adhesives bind dirt and make maintenance more difficult. First clean with Lithofin FZ Cement Residue Remover as described on Page 1. Synthetic grouting materials can be removed with Lithofin FZ Intensive Cleaner (undiluted, approx. 20 minutes working time). Scrub using a white pad on polished surfaces and a green pad on rough, matt surfaces.

## 1 Cleaning and refurbishing used or extremely dirty surfaces

- ◆ Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.
- ➔ Dilute Lithofin FZ Intensive Cleaner up to 1:10, apply using a scrubbing brush or a white pad and allow to work for 5 to 10 minutes. Scrub well with a scrubbing brush or machine and wait 5 more min. Add water and remove the solution with a mop or a wet-and-dry vacuum.
- ➔ Rinse twice with plenty of clear water until all product residues are removed.
- ◆ Allow the surface to dry for 24 to 48 hours before applying a protective treatment.



## Other, stubborn types of dirt

grease, oil, wax, varnish, paint, ink, rubber streaks, polymer layers, etc.	Lithofin WAX-OFF
protective polymer coatings, pencil marks	Lithofin Abra-CLEAN
calcium deposits, rust discolouration	Lithofin KF Active-Clean
in very stubborn cases, a white pad may bring better results.	

## 2 Additional information about protective treatments

- ◆ Despite the outstanding properties of porcelain tiles, staining may occur.
- ◆ Lithofin FZ Stain-Stop reduces the sensitivity of the porcelain tile and the grout lines and facilitates maintenance.
- ◆ This treatment is recommended for newly installed polished surfaces. Test the product's suitability on matt or structured surfaces prior to use.

### Please Note:

- ◆ **Always test the product in an inconspicuous area.** Non-absorbent or wet surfaces cannot be treated.
- ◆ Use impregnators only on completely dry surfaces. Otherwise, the product will not be able to penetrate into the surface.
- ◆ Do not allow the product to dry on the surface. Carefully remove all excess while wet. In case the product is beginning to dry, re-dissolve with Lithofin FZ Stain-Stop >W<.

## 3 Additional care

- ◆ Surfaces subject to heavy wear and tear occasionally require a more intensive cleaning.
- ◆ Dilute Lithofin FZ Intensive Cleaner up to 1:10 with cold or lukewarm water. Apply with a scrubbing brush, allow to work for 10 to 20 minutes, and then remove the cleaning solution from the surface. Rinse with clear water and allow to dry.
- ◆ Some surfaces should be cleaned with Lithofin KF Active-Clean (diluted approx. 1:20) every once in a while to remove calcium deposits.

### Please Note:

- △ Please follow the detailed instructions on the label.
- △ Greasy or waxy maintenance products may bind dirt and will affect the slip resistance properties of the surface.

If you require advice or are in any way unsure about these instructions, please call our

**Technical Support Line at**

**AUS: (03) 8552 6000 / NZ: (9) 4433932**

This information should be considered to be informal and non-binding.  
The products must be used according to local conditions and materials.  
Instructions must be read carefully and followed closely. Always test  
the products in an inconspicuous area. (AUS/NZ7.11gps/6.11)

Your LITHOFIN-Dealer:

## The Professional Solution

**Australia:** CDK Stone Pty. Ltd • 4-6 Freighter Rd. • Moorabbin, VIC 3189 • Phone (03) 8552 6000 • Fax (03) 8552 6001

**New Zealand:** CDK Stone NZ Ltd. • 11/46 Ellice Road • Glenfield • Auckland • Phone (9) 4433932 • Fax (9) 443 3931

**Manufactured in Germany by:** LITHOFIN AG • 73240 Wendlingen • e-mail: info@lithofin.de

**www.lithofin.com**